

UNITED STATES PATENT APPLICATION

of

Sani El-Fishawy

for

**FLOOR CONTROL MANAGEMENT IN
NETWORK BASED INSTANT CONNECT COMMUNICATION**

WORKMAN NYDEGGER
A PROFESSIONAL CORPORATION
ATTORNEYS AT LAW
1000 EAGLE GATE TOWER
60 EAST SOUTH TEMPLE
SALT LAKE CITY, UTAH 84111

FLOOR CONTROL MANAGEMENT IN NETWORK BASED INSTANT CONNECT COMMUNICATION

BACKGROUND OF THE INVENTION

1. The Field of the Invention

[01] The present invention relates to wireless and wireline voice communication over networks. More specifically, the present invention relates to floor control management between devices engaging in network based, half-duplex instant connect voice communication.

2. The Relevant Technology

[02] During recent years, various forms of mobile communication devices using radio signals have become more widely used. An early example of mobile communication, and one which has been in use for decades, is two-way radio devices, commonly known as “walkie-talkies.” Conventional walkie-talkies have a range of up to several thousand meters and transmit voice signals over a selected radio frequency. A transmitting walkie-talkie can communicate with another, recipient walkie-talkie that is within the transmitting range and is tuned to the selected frequency. Walkie-talkies have been widely used in industrial, construction and recreational settings.

[03] One of the convenient features of walkie-talkies is the ability to immediately initiate communication with recipients without requiring the user who initiates the communication to input a telephone number or to wait while call setup is performed. Instead, the user merely presses a button on the mobile communication device and begins speaking. Any recipient device that is within range and is tuned to the selected frequency immediately receives the voice data. The receiving party can immediately receive the communication without having to

respond to a ring or other audible signal, such as those that have been associated with the act of answering a ringing telephone.

[04] A typical walkie-talkie communication session occurs when participating devices are tuned in to a particular radio frequency. The communication session is a half-duplex event, wherein the data can only flow in one direction at a time. In such communication sessions, the right or ability to transmit data is known as “having the floor”. Management of the floor is important in any half-duplex communication session to indicate the direction of data flow and to avoid confusion on part of the participants that might arise if both parties attempt to speak at the same time. In conventional walkie-talkies, the floor is obtained by one of the mobile devices when the user presses the “talk” button on his device. The party who has the floor can speak into the device and transmit the resulting voice data to the recipient. In this sense, the party having the floor is designated herein as being the “sending” party, while the party who does not have the floor is referred to herein as being the “receiving” party.

[05] During the past few years, consumer electronics companies have introduced highly-popular personal walkie-talkies. Such personal walkie-talkies are widely used in recreational and family situations, as well as by industrial and commercial users. The advantages of the newer personal walkie-talkies include lower cost and the ability to easily select from fifty or more communication channels. Personal walkie-talkies do not require the user to enter a telephone number or wait during call setup and the receiving party can immediately receive voice data without having to answer a ringing telephone. However, personal walkie-talkies also operate in half-duplex mode over a selected radio frequency and are characterized by a lack of security, limited range, and the same floor control patterns as conventional walkie-

talkies. Nonetheless, personal walkie-talkies have been a successful consumer electronics product.

[06] Cellular or mobile telephones are another example of mobile communications devices whose use has become widespread during recent years. Unlike walkie-talkies, mobile telephones operate over a network using a full-duplex communication channel that uses code-division or time-division multiplexing. Because of the full-duplex nature of the communication, floor control is not a significant issue in mobile telephone communication. Both parties to a mobile telephone call have the ability to simultaneously send and receive voice data at any time during the call. In addition, mobile telephone communication has an essentially unlimited range and is highly secure because of the call setup routines and the multiplexing of the communication channels. Typical mobile telephone communication requires entering a multi-digit telephone number, waiting during call setup, and manually activating the receiving mobile device in response to a ring or other audible signal indicating that a call is incoming.

[07] The convergence of walkie-talkie radio communication and mobile telephone communication is often referred to as “push-to-talk”, which offers a near instant connection and two-way communication between users. Communication can be one-to-one or one-to-many. One example of a push-to-talk system is Nextel’s iDEN-based Push to Talk[®] (also known as Direct Connect[™]) service that has become very popular over the past several years. Push-to-talk systems may also be implemented using standard voice-over Internet protocol (VoIP) technologies or other IP telephony technologies, wherein voice information is sent in digital form over IP-based data networks. Such push-to-talk systems are hereinafter referred to as “network-based instant connect systems”, and they can be deployed on many types of

networks, including wireless and wireline networks. A network-based instant connect call is a telephone call established using a network, but in a way that is designed to give the user the experience of a conventional or personal walkie-talkie call. For instance, in wireless networks, network-based instant connect calls are initiated when the user selects a recipient from a contact list on the mobile device and presses the talk button. Likewise, network-based instant connect calls are received by automatically activating the receiving device for immediate output of voice data without requiring the recipient to manually respond to a ring or other audible signal. Because the network-based instant connect call is typically established over a wireless network, the call requires numbers that identify the participating mobile devices, such as telephone numbers, and a call setup routine. Unlike conventional walkie-talkie communication, network-based instant connect calls have essentially unlimited range and security features of a conventional mobile telephone call.

[08] Although wireless networks on which network-based instant connect calls are typically carried inherently have full-duplex capabilities, floor control is usually moderated so as to mimic the conventional walkie-talkie experience. In particular, the user who presses the talk button on a suitably enabled mobile device obtains the floor and can send voice data until the button is released. The recipient of the voice data who does not have the floor can merely receive the voice data and cannot take the floor until the other party relinquishes the floor.

[09] Since these techniques for floor control in network-based instant connect calls mimic the conventional walkie-talkie user experience, the resulting conversation between the calling parties also suffers from the inherent drawbacks of communicating in the style of a walkie-talkie. In typical wireline and mobile telephone calls, the full-duplex nature of the communication permits the conversing parties to engage in normal, spontaneous two-way

conversation, including the patterns of feedback, response, and interruption that are similar to those associated with face-to-face communication. In contrast, network-based instant connect conversations are characterized by successive periods during which the floor is held by alternating parties until such time that these parties relinquish the floor by releasing the talk button. Such conversations do not permit the conversing parties to engage in the two-way speech patterns that are part of normal face-to-face or telephone conversations. Thus, network-based instant connect conversations are somewhat unnatural and difficult, particularly for those who do not have significant experience using walkie-talkies.

SUMMARY OF THE INVENTION

[010] The present invention is directed to the management of the floor allocated between the devices of calling parties in network-based instant connect communication. The floor control methods of the invention can be applied to network-based instant connect calls that are established in conventional ways. A network-based instant connect call is initiated when the calling party uses a network-based instant connect device to initiate a communication session over a network to a designated recipient device. The calling party obtains the floor at the initiation of the call by pressing the talk button. In this regard, the network-based instant connect call has been initiated and set up in a manner similar to existing network-based instant connect techniques.

[011] According to the invention, the floor allocated among the devices of the calling parties is controlled in a way that facilitates patterns of two-way conversation that are common to face-to-face and typical full-duplex telephone conversations, but have been absent in conventional network-based instant connect calls. In general, the floor is controlled according to the invention in a way other than permitting the party having the floor to maintain it so long as the party continues to press the talk button. According to a first method associated with the invention, the receiving party who does not have the floor can transfer the floor away from the sending party by pressing the talk button on the network-based instant connect device used by the recipient. In this way, the receiving party can take the floor at a time of its choosing rather than being forced to wait until such time that the sending party relinquishes the floor by releasing the talk button.

[012] A significant benefit of this floor control technique is that a receiving party can respond to, provide feedback to, or interrupt the sending party at any time regardless of whether the

sending party chooses to relinquish the floor. This permits a half-duplex, network-based instant connect call to exhibit the casual, two-way conversation patterns that have been absent in conventional network-based instant connect calls. Additionally, the ability to “interrupt” a sender and take the floor is particularly useful during group network-based instant connect calls since multiple speakers may desire to interject a remark or otherwise acknowledge a speaker at any time during the communication session, thereby enhancing the interactivity of the group’s communication.

[013] Another benefit of this technique for floor control is that existing network-based instant connect systems can be readily adapted to operate in this manner. Existing network-based instant connect systems have mechanisms for detecting the talk button of the sending party having been pressed, thereby allocating the floor to the sending party. According to this floor control technique, the network-based instant connect system detects the event of the talk button of the receiving party being pressed as a signal to transfer the floor away from the sending party to the receiving party. The other attractive features of conventional network-based instant connect calls are present, including call security, extended communication range, the existence of a talk button that is used during the network-based instant connect call, and the automatic and immediate receipt of voice data at the receiving device without requiring the receiving party to manually respond to a ring or other audible signal.

[014] According to a second method of the invention, the floor is managed by transitioning from half-duplex communication to full-duplex communication at some point after the network-based instant connect call is established. The transition to full-duplex communication, which is inherently supported by the network, eliminates the need for sequential floor transitions between the calling parties. For instance, after the network-based instant connect

call is initiated and a receiving party responds thereto, the call can be transitioned from half-duplex communication to full-duplex communication. This transition can be initiated in a way that is transparent to the calling parties, other than the fact that, once it is complete, the calling parties can then engage in ongoing two-way communication that is similar to that of a typical telephone call. For example, a preference to automatically transition to full-duplex communication once both parties are communicating can be specified such that the transition to full-duplex communication happens automatically without the need for either user to intervene. Alternatively, the transition can occur after one or both parties manually indicate to the network-based instant connect device to send a request to make the transition. This could occur by pressing one or more keys on a device keypad, pressing soft keys on the device or by speaking a recognized voice command.

[015] These techniques of the invention enhance the practical usability of network-based instant connect calls and network-based instant connect systems. The beneficial and attractive features of network-based instant connect calls are maintained, while eliminating the unnatural speech and conversation patterns that have been characteristic of network-based instant connect calls. Existing network-based instant connect systems can be adapted to operate with the invention, which means that the existing infrastructure investments that have been made by companies who offer network-based instant connect services can be leveraged to improve the communication services offered to customers.

[016] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the invention. The features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the

appended claims. These and other features of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

WORKMAN NYDEGGER
A PROFESSIONAL CORPORATION
ATTORNEYS AT LAW
1000 EAGLE GATE TOWER
60 EAST SOUTH TEMPLE
SALT LAKE CITY, UTAH 84111

BRIEF DESCRIPTION OF THE DRAWINGS

[017] In order that the manner in which the advantages and features of the invention are obtained, a particular description of the invention will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not, therefore intended to be considered limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

[018] Figure 1 is a block diagram illustrating a wireless network in which the network-based instant connect communication systems of the invention may be practiced.

[019] Figure 2a is a flow diagram depicting a method by which the floor is reassigned when a receiving party presses the talk button of a network-based instant connect device.

[020] Figure 2b is a flow diagram illustrating a method by which the floor is reassigned when a receiving party taps the talk button of a network-based instant connect device.

[021] Figure 3 is a flow diagram illustrating a method by which a network-based instant connect call is transitioned from half-duplex to full-duplex to eliminate the floor control requirements of the network-based instant connect call.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[022] The present invention is directed to systems and methods for controlling the floor that is allocated between devices engaged in network-based instant connect communication. In general, the methods of the invention permit a party to initiate the transmission of voice data in a network-based instant connect communication session without waiting for the remote party to relinquish the floor. According to a first embodiment of the invention, the party takes the floor from the remote party by pressing a talk button on the network-based instant connect device or otherwise generating a floor request signal. The floor is taken in this manner without requiring the remote party to give up the floor or otherwise give consent to the floor being given to the other party.

[023] According to a second embodiment of the invention, the need to allocate the floor between the calling parties is eliminated by transitioning the network-based instant connect call from half-duplex communication to full-duplex communication. This transition can take place after a receiving party has provided input that indicates that the network-based instant connect call has been accepted. According to either of these techniques, the parties engaged in network-based instant connect communication can interrupt, respond to, or otherwise provide feedback to each other in ways that are similar to the conversation patterns of telephone calls as opposed to those that have been previously associated with network-based instant connect calls.

1. Network-based Instant Connect Systems

[024] In order to describe the various methods of the invention, Figure 1 illustrates an example of network 100 in which the invention can be practiced. It is to be understood that the network of Figure 1 represents only an example of the suitable environments in which the

invention can be implemented, and that other network architectures, including wireline networks, are possible. Network 100 includes one or more wireless telephone networks that operate with network-based instant connect devices 102 and 104. In the illustrated example, device 102 operates within cellular network 200a, while device 104 operates within cellular network 200b.

[025] Figure 1 illustrates base station 106 in cellular network 200a that communicates with network-based instant connect device 102 by transmitting and receiving radio signals 108. Base stations 106 and other base stations in network 200a operate over respective regions or cells within which the radio signals 108 are sufficiently strong to provide reliable communication. In cellular networks, a grid of partially overlapping cells is positioned in a geographic area to provide service for the network-based instant connect devices anywhere in the range of the cells. Base station 106 may operate under the control of associated base station controllers 112, which may in turn be coupled with a packet data serving node (PDSN) 116. Base station 106 may also be coupled with a mobile switching center 114, which enables device 102 to communicate with the public switched telephone network (PSTN) 130.

[026] In network 100 of Figure 1, network-based instant connect device 102 may acquire radio connectivity and IP network connectivity in a manner well known in the art. For example, device 102 may issue an origination request to mobile switching center 114, which may send the request back to BSC 112. BSC 112 may assign a traffic channel to device 102, or it might forward the request to PDSN 116, which works with device 102 to establish a data link by which voice and data is transmitted to and received from the device. Device 102 may then initiate and participate in network-based instant connect communication sessions with the assistance of a PDSN 116, which provides device 102 with a gateway to IP network 118. The

voice data from device 102 is then delivered to a network-based instant connect application server 120, which among other functionality, may be responsible for arbitrating and managing floor control allocation.

[027] Alternatively, rather than floor control being arbitrated by a network element such as an instant connect application server, the logic to implement floor control allocation may be resident on the network-based instant connect device, in which case the participating devices decide who controls the floor. In Figure 1, since the other network-based instant connect device 104 is located within the range of a cellular network 200b, the base station controller 212 and associated PDSN 216 are used to establish the communication between the devices 102 and 104. Network-based instant connect device 104 acquires radio connectivity and IP network connectivity with the assistance of the associated BSC 212 and PDSN 216 as described previously. In this way, the network-based instant connect devices 102 and 104 can communicate with substantially any other compatible network-based instant connect devices that are located in the interoperating cellular networks, such as networks 200a, 200b, etc.

[028] It should be understood that this and other arrangements and processes described herein are set forth for purposes of example only, and other arrangements and elements (e.g., machines, interfaces, functions, orders of elements, etc.) can be added or used instead and some elements may be omitted altogether. Further, those skilled in the art will appreciate that many of the elements described herein are functional entities that may be implemented as discrete components or in conjunction with other components, in any suitable combination and location, and by software, firmware and/or hardware.

[029] Network-based instant connect calls in network 100 are designed to give the calling parties an experience similar to those that are associated with the use of a conventional or

personal walkie-talkie. Network-based instant connect devices 102 and 104 have talk buttons 202 and 204, respectively. The talk buttons are used to initiate the transmission of voice data from the corresponding network-based instant connect devices in ways that are described herein in reference to Figures 2a, 2b and 3. In general, network-based instant connect calls are initiated when the user selects a recipient and presses the talk button. Network-based instant connect calls are received as the receiving device is automatically activated and caused to output the incoming voice data without requiring the recipient to manually respond to a ring or other audible signal. Network-based instant connect calls have the essentially unlimited range and security features of a conventional mobile telephone call.

[030] Although the cellular networks 200a and 200b on which network-based instant connect calls are carried inherently have full-duplex capabilities, network-based instant connect calls are transmitted, at least initially, using half-duplex communication so as to mimic the walkie-talkie experience. The use of the half-duplex communication means that data can travel in only one direction at any given time. In order to indicate to the system in which direction voice data should be sent, network-based instant connect devices 102 and 104 may utilize a “talk” button or other user input mechanism which causes the floor to be allocated to one party. The device that has the floor has the ability to transmit voice data, whereas the device that does not have the floor can only receive the data. As described in Figures 2a, 2b and 3, the methods of the invention enable the party without the floor to initiate the transmission of voice data without waiting for the remote party to relinquish the floor. These methods can be performed in existing cellular networks (e.g., networks 200a and 200b) that have network-based instant connect capabilities as well as with existing network-based instant connect devices that have been adapted to perform the acts disclosed herein.

2. Floor Transfer Methods

[031] Figure 2a is a flow diagram that illustrates a method according to a first embodiment of the invention for transferring the floor to a recipient device in response to user input provided to the recipient device. This method is described in reference to Figure 1, in which network-based instant connect device 102 is designated as a first device or a sending device, and network-based instant connect device 104 is designated as a second device or a receiving device. According to this embodiment, the floor is taken by a device in the network-based instant connect communication session when a floor request signal is generated by the device, one example of which involves the talk button of the device being pressed and held down, tapped, or otherwise engaged. In Figure 1, the periods of time during which the talk buttons of the respective devices are pressed are shown at bars 222, 228, 234 and 240, while the crosshatched regions of these bars indicate the allocation of control between devices 102 and 104.

[032] The example illustrated in Figure 2a begins at act 220, in which the first device initiates a network-based instant connect call, obtains the floor, and sends voice data to the second device. The network-based instant connect call can be initiated as described herein, by the user of the first device selecting a recipient, pressing the talk button at time T_0 and speaking into the first device. Bar 222 of Figure 2a indicates that the talk button is pressed by the user of the first device between time T_0 and T_2 . The crosshatched region of bar 222 between time T_0 and T_1 indicates that the first device has the floor. During this time period, the second device receives the data in act 224.

[033] At time T_1 , the user of the second device decides to take the floor and does so by generating a floor request signal originating at the second device. This floor request signal is generated in this example by the user pressing the talk button of the second device in act 226. The floor request signal is transmitted to a network-based instant connect server in the wireless communication network 100 of Figure 1. The floor request signal results in the floor being transferred from the first device to the second device. Alternatively, in the case where floor control logic is resident on the device, the floor control signal may be transmitted directly to the second device which results in the floor being transferred from the first device to the second device.

[034] Bar 228 of Figure 2a indicates that the talk button of the second device is pressed between time T_1 and T_4 . The floor is transferred to the second device at time T_1 in response to the floor request signal, notwithstanding the fact that the floor is held by the first device up to time T_1 and that, at time T_1 , the talk button of the first device continues to be pressed as shown at bar 222. Thus, the transition of the floor from the first device to the second device at time T_1 represents, for instance, the user of the second device interrupting or spontaneously responding to the other user without waiting for the first device to relinquish the floor. This facilitates the conversational two-way communication that has not previously been possible in network-based instant connect systems. It is noted that the floor is transferred at time T_1 from the first device to the second device without the first device providing consent thereto. Moreover, region 222' from time T_1 to T_2 shows that the talk button of the first device continues to be pressed for a short period of time just after the loss of the floor, indicating that the floor transition may have been unexpected by the user of the first device.

[035] The crosshatched region of bar 228 between time T_1 and T_3 indicates that the second device has the floor. During this time period, the first device receives data in act 230. The first device, which has just lost the floor, has the ability to retake it by generating a floor request signal at time T_3 . This floor request signal associated with the first device can also be generated by pressing the talk button, as shown in act 232. Bar 234 indicates that the talk button of the first device is pressed between time T_3 and T_5 . The floor is transferred to the first device at time T_3 in response to the floor request signal, notwithstanding the fact that the floor is held by the second device up to time T_3 and that, at time T_3 , the talk button of the second device continues to be pressed as shown at bar 228. This transition can also represent an interruption, feedback, or a response to the other party, which can be part of an ongoing, two-way conversation between the parties. This transition is initiated by the first device without waiting for the second device to relinquish the floor and without the second device providing consent thereto. Moreover, region 228' from time T_3 to T_4 shows that the talk button of the second device continues to be pressed for a short period of time just after the loss of the floor, indicating that the floor transition may have been unexpected by the user of the second device.

[036] The crosshatched bar 234 between time T_3 and T_5 designates the floor being held by the first device. During this time period, the second device receives data in act 236. Although the first two floor transitions of Figure 2a are associated with interruption events, the floor can also be transferred to one of the parties after the other party has relinquished it. At time T_5 , the user of the first device relinquishes the floor when, for instance, the user of the first device has finished speaking and releases the talk button. During the period of time from time T_5 and T_6 , neither device has the floor. In this situation, either party can take the floor by pressing its talk button. In the example of Figure 2a, the second device takes the floor at time T_6 by pressing

the talk button in act 238. During the period after T_6 when the second device has the floor, the first device 242 continues to receive data.

[037] Figure 2 illustrates various principles associated with this embodiment of the invention. In particular, a device that does not hold the floor can take it when the user generates a floor request signal by pressing the talk button of the device. If the other party has the floor when the floor request signal is generated, the other party loses the floor. As shown in Figure 2a, this process facilitates two-way conversation patterns, including potential interruptions at time T_1 and T_4 .

[038] In an alternate implementation illustrated in Figure 2b, the floor is transferred in response to a floor request signal that is generated at one of the devices in response to the user tapping the talk button. As used herein, a “tap” of a talk button is the act of pressing the talk button, followed shortly thereafter by the release of the talk button. In this method, the user who obtains the floor by pressing and releasing, or tapping, the talk button can maintain the floor thereafter without being required to continually maintain the talk button in the depressed position. The user obtains the floor by the initial act of pressing the talk button and loses the floor only when the remote user requests the floor.

[039] The steps illustrated in Figure 2b are substantially the same as those in Figure 2a, except for the manner in which the users tap the talk button in Figure 2b rather than pressing and holding in Figure 2a. In Figure 2b, the crosshatched regions 244, 246, 248 and 250 show the tapping of the talk button, while the open regions 244', 246', 248', 250' show the time during which the devices maintain the floor after a tap.

[040] The embodiments of Figures 2a and 2b are also extended to wireline networks and wireline devices in which floor control occurs. For example, the floor control in a wireline-

based speakerphone is typically triggered when a sensor on the speakerphone detects voice. This method can be problematic in an environment where there is audible background noise. Such noise may tend to spuriously and erroneously trigger a floor control transition when one was not intended. Additionally, problems occur when a speaker continues to speak at a rate and a volume that does not allow another speaker on the conference call to take control of the floor. The use of a button or one or more keys on the speakerphone keypad to explicitly allocate floor control can be applied to the use of such a speakerphone. In any of these situations, the method of the present invention may further be employed in this context to improve the call experience. A speaker who does not currently hold the floor can press one or more keys on the telephone to “interrupt” the speaker holding the floor, to interject a comment or otherwise reallocate the floor.

3. Transition to Full-Duplex Communication Channel

[041] In the embodiment illustrated in Figure 3, the need for floor allocation is eliminated by transitioning the network-based instant connect call from half-duplex communication to full-duplex communication. Conventional network-based instant connect calls are conducted as half-duplex communication in cellular networks that have the inherent ability to conduct full-duplex telephone calls.

[042] The example of Figure 3 begins at act 310, in which the first device initiates a network-based instant connect call which is half-duplex, obtains the floor, and sends data to the second device. The initiation of the network-based instant connect call can be similar to the process described in reference to the call of Figure 2a. The user of the first device selects a recipient, presses the talk button at time T_0 and speaks into the first device. Bar 312 indicates that the

talk button is pressed by the user of the first device between time T_0 and T_2 . The crosshatched region of bar 312 between time T_0 and T_1 shows that the first device has the floor. During this time period, the second device receives the data in act 224, during which time the network-based instant connect call continues to be conducted using half-duplex communication. Immediately after time T_0 , the recipient of the network-based instant connect call becomes aware of the call when the second device begins outputting the voice data. This activation of the second device to output the data is automatic and does not require the user to respond to a ring or other audible signal.

[043] At time T_1 , the user of the second device has decided to engage in the network-based instant connect communication session and expresses this decision in act 316 by pressing the talk button at time T_1 . At this point, this input causes the network to transition from the original half-duplex call to a full-duplex call. The transition to a full-duplex call permits the parties to engage in ongoing two-way communication in acts 316 and 320, providing a conversation experience similar to that of mobile telephone calls. Because the full-duplex communication is used after time T_1 , floor allocation is not needed, and both parties can send voice data at any time without pressing the talk button. Thus, the first device can continue to send data after time T_1 and T_2 (region 312') as well as after releasing the talk button at time T_2 . Similarly, the second device can continue to send data after releasing the talk button at time T_3 .

[044] The network-based instant connect call established as shown in Figure 3 exhibits the primary advantages of conventional network-based instant connect calls while eliminating the main inconveniences that have been experienced. In particular, such network-based instant connect calls can be received immediately by the recipient without having to respond to a ring or another audible signal. In addition, the need to continue to press the talk button when

speaking and to wait while the other party holds the floor is eliminated when the transition to the full-duplex communication channel is made. This and the other embodiments of the invention are also capable of being practiced in existing networks and with existing network-based instant connect devices that are adapted to perform the methods disclosed herein.

[045] The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

WORKMAN NYDEGGER
A PROFESSIONAL CORPORATION
ATTORNEYS AT LAW
1000 EAGLE GATE TOWER
60 EAST SOUTH TEMPLE
SALT LAKE CITY, UTAH 84111